

The following Listing of Claims will replace all prior versions, and listings, of claims in the application.

**LISTING OF CLAIMS:**

1. (Previously Presented) A pump unit comprising:
  - a first fixed-capacity pump having large capacity;
  - a second fixed-capacity pump having small capacity that is smaller than that of the first fixed-capacity pump;
  - a first discharge line connected to the first fixed-capacity type pump;
  - a second discharge line connected to the second fixed-capacity type pump;
  - a variable-speed motor arranged for driving the first and second fixed-capacity type pumps;
  - a switching valve arranged to selectively connect or disconnect the first discharge line and the second discharge line with each other;
  - a pressure sensor arranged to detect a pressure of the second discharge line; and
  - a control device arranged to receive a signal from the pressure sensor and a signal representing a rotational speed of the variable-speed motor, the control device being configured to control the switching valve and the variable-speed motor so that operation is selectively performed in a first mode in which the first discharge line and the second line are disconnected with each other to make the first fixed-capacity type pump unloaded such that a constant-horsepower operation is performed, and a second mode in which the first discharge line and the second discharge line are connected with each other such that a constant-horsepower operation is performed.

2. (Previously Presented) The pump unit according to Claim 1, wherein the control device is configured to switch the switching valve from a connecting state to a disconnecting state when the rotational speed of the variable-speed motor has decreased below a predetermined set rotational speed, and switch the switching valve from the disconnecting state to the connecting state when the pressure detected by the pressure sensor has decreased below a predetermined set pressure.

3. (Previously Presented) The pump unit according to Claim 1, wherein the control device is configured to switch the switching valve from a disconnecting state to a connecting state when the rotational speed of the variable-speed motor has increased over a predetermined set rotational speed, and switch the switching valve from the connecting state to the disconnecting state when the pressure detected by the pressure sensor has increased over a predetermined set pressure.

4. (Previously Presented) The pump unit according to Claim 1, wherein the control device includes an input section from which the predetermined set rotational speed and the predetermined set pressure are variably inputted so that the first mode and the second mode are operable in a plurality of modes, respectively.

5. (Previously Presented) The pump unit according to Claim 2, wherein the control device includes an input section from which the predetermined set rotational speed and the predetermined set pressure are variably inputted so that the first mode and the second mode are operable in a plurality of modes, respectively.

6. (Previously Presented) The pump unit according to Claim 3, wherein  
the control device includes an input section from which the predetermined set  
rotational speed and the predetermined set pressure are variably inputted so that the first  
mode and the second mode are operable in a plurality of modes, respectively.